

EC Declaration of Performance Murfor® +

CUSTOMER INFORMATION

- Unique identification code of the product: **Murfor® +**
with different material coating references and widths - product types see table 1.
- Type- and traceability info, allowing identification of the construction product as required pursuant to Article 11(4): is provided on the product packaging and product label.
- Intended use of the construction product in accordance with EN 845-3: 2012: Welded wire meshwork bed joint reinforcement in **STRUCTURAL USES** in wall and partitions as covered in the scope of EN845-3: 2012.
- Name, registered trade name and contact address of the manufacturer as required pursuant to Article 11(5): **NV BEKAERT SA** Bekaertstraat 2, B-8550 Zwevegem, Belgium.
- Not applicable.
- System of assessment and verification of constancy of performance of the construction product:
System n°3
- Notified Lab:
- TSUS registration nr : 1301. Studená 3, 821 04 Bratislava, Slovak Republic..

Performed: Initial Type Testing and issued ITT report,
- ITT report 20-12-0412.
- Not applicable.
- Declared performance:
the essential characteristics per product type are listed in table 1.
- The performance of the products identified in points 1 and 2 and listed in table 1, are in conformity with the declared performance in point 9.
This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Paul De Geyter, senior Quality manager NV Bekaert SA.

EC Declaration of Performance Murfor® +

CUSTOMER INFORMATION

Addendum to pt 9. Declared Performance on essential characteristics – see table 1

Table 1: Declaration on essential characteristics per Murfor® + product type - according EN 845-3: 2012

Product type	Murfor® + Z /3,65	Murfor® + S/3,65	Murfor® + Z /4,56
Type of welded steel wire meshwork	Truss		
Intended use	Welded wire meshwork bed joint reinforcement in structural uses in wall and partitions as covered in the scope of EN845-3: 2012.		
Dangerous substances	None		
Diameter + tol. longitudinal wire (mm)	3,65 ± 0,10		4,56 ± 0,10
Diameter + tol. cross wire (mm)	3,0 ± 0,10		3,75 ± 0,10
Length + tol. (mm)	3050 ± 1,5%		
Pitch + tol. (mm)	406 ± 3%		
Width + tol (mm)	50, 100, 150, 200 ± 5	50 ± 5	200, 250 ± 5
Material/coating reference	R20	R3	R20
Ductility class Agt (%) - Rm/Rp0,2	LOW 0,8 - 1,03	NORMAL	LOW 0,8 - 1,03
Shear load capacity of welds (N)	> 3000		
Characteristic Yield Strength (N/mm²) Longitudinal wires	600	600	600
Characteristic Yield Strength (N/mm²) Cross wire	600	520	600
Bond strength (kN) with related bond length (mm)	12,56 kN on 244mm		
Anchorage length (mm)	244mm		
Masonry units and mortar	masonry units $f_b \geq 5 \text{ N/mm}^2$ and general purpose mortar $\geq \text{M5}$		