

Technische data



Glasvezeltape FIBA® | Classic

Drager			
Type		Glasvezel weefsel	
Maaswijdte		2,7 x 2,7 mm	
Gewicht		63	g/m²
Lijm			
Type		Waterbasis acrylaat	
Samenstelling			
Dikte (totaal)		300	µ (micron)
Coating en lijm		± 45	%
Mechanische eigenschappen			
Treksterkte	Lengte	437	N/50 mm
	Breedte	919	N/50 mm
Bijzonderheden			
Alkalibestendig		Nee	
Norm		CE (DoP verklaring – zie blad 2)	
Tolerantie		5% op alle waarden	
Aanvullende opmerking(en)			

Land van herkomst	Czech Republic
Statistiek code	70195100
In overeenstemming met RohS	Ja



Verwerking
Aanbrengen op een schone, droge, stof- en vetvrije ondergrond.

Opslag
In de originele verpakking, bij een temperatuur van max. 21°C en een luchtvochtigheid van max. 50% en uit de buurt van een warmtebron of direct zonlicht.

Disclaimer
De vermelde data is uitsluitend informatief. Voor speciale toepassingen adviseren wij u het materiaal zelf te testen of contact met ons op te nemen.

Van Duinen TechnoTape B.V.
Pieter Zeemanweg 120
NL-3316 GZ DORDRECHT
Netherlands

T +31 (0)78 651 20 55
F +31 (0)78 618 50 26
E info@technotape.nl
I www.technotape.nl

Document	TDS-00095
Versie	002
Revisie datum	25-03-2019

Declaration of Performance

nr. DOP – 3 – FIBATAPE – 01

1.	Unique identification code of the product-type:	P – 3 – FIBATAPE
2.	Product:	FibaTape®
3.	Intended use of construction product:	Glass fibre joint tape for gypsum plasterboards
4.	Manufacturer:	SAINT-GOBAIN ADFORS CZ, s.r.o. Sokolovská 106 570 01 Litomyšl Czech Republic
5.	System of assessment:	System 3
6.	European Assessment Document: European Technical Assessment: Technical Assessment Body:	EAD 070002-00-0505: 2016 ETA-09/0075 of 02.07.2018 TECHNICKÝ A ZKUŠEBNÍ ÚSTAV STAVEBNÍ PRAHA, s.p.

Declared performance:

Essential characteristics	Performance
Reaction to fire	NPD
Tensile strength (standard conditions 23± 1°C)	$\sigma_k = 15 \text{ N/mm}$
Resistant to dampness	$\sigma_k = 9 \text{ N/mm}$ 37%
Self-Adhesion ability (low and high temperature)	no visual changes and other defects
Jointing material penetration ability	57 N

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

In Litomyšl, date 02.07.2018



Erik Pellati, Product Manager